

AXIS M3115-LVE Network Camera

Affordable flat-faced 1080p dome with IR

AXIS M3115-LVE is an affordable, flat-faced dome designed to suppress light reflections. This compact, IK08-rated camera features a wide-angle view in HDTV 1080p video. It includes Forensic WDR, Lightfinder and built-in IR illumination for sharp video with clear colors even in challenging light or complete darkness. Additionally, it offers flexible installation for both indoor and outdoor surveillance. And, with its 3-axis camera-angle adjustment, it can be easily leveled and directed. It features enhanced security functionality, and Axis Zipstream with support for H.264/H.265 significantly reduces bandwidth and storage requirements without compromising image quality.

- > **HDTV 1080p video quality**
- > **Forensic WDR, Lightfinder and IR illumination**
- > **Flat-faced design suppressing light reflections**
- > **Zipstream supporting H.264 and H.265**
- > **Signed firmware and secure boot**



AXIS M3115-LVE Network Camera

Camera		Event actions
Image sensor	1/2.9" progressive scan RGB CMOS	Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share, and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP, and SNMP trap Overlay text
Lens	2.8 mm, F2.0 Horizontal field of view: 105° Vertical field of view: 58° Fixed iris, Fixed focus, IR corrected	
Day and night	Automatically removable infrared-cut filter	
Minimum illumination	Color: 0.17 lux at 50 IRE, F2.0 B/W: 0.03 lux at 50 IRE, F2.0 0 lux with IR illumination on	
Shutter time	1/33500 s to 2 s	
Camera angle adjustment	Pan: ±180° Tilt: 0° to 60° (0° = lens directed at a right angle to camera base) Rotation: ±95° Can be directed in any direction and see the wall/ceiling	
Video		
Video compression	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG	
Resolution	1920x1080 to 160x90	
Frame rate	Up to 25/30 fps with power line frequency 50/60 Hz	
Video streaming	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265	
Multi-view streaming	Up to 2 individually cropped out view areas in full frame rate	
Image settings	Compression, color saturation, brightness, sharpness, contrast, local contrast, white balance, day/night threshold, tone mapping, exposure control (including automatic gain control), exposure zones, Forensic WDR: up to 120 dB depending on scene, fine tuning of low-light behavior, defogging, dynamic text and image overlay, privacy masks, mirroring, rotation: 0°, 90°, 180°, 270° including Corridor Format	
Pan/Tilt/Zoom	Digital PTZ	
Audio		
Audio input/output	Two-way audio connectivity via the optional AXIS T61 Audio and I/O Interfaces with portcast technology	
Network		
Security	Password protection, IP address filtering, HTTPS ^a encryption, IEEE 802.1x (EAP-TLS) ^a network access control, Digest authentication, User access log, Centralized Certificate Management, brute force delay protection, signed firmware, secure boot	
Supported protocols	IPv4, IPv6 USGv6, HTTP, HTTP/2, HTTPS ^a , SSL/TLS ^a , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP [®] , SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMP, RTCP, ICMP, DHCPv4/v6, ARP, SOCKS, SSH, SIP, LLDP, MQTT, Syslog	
System integration		
Application Programming Interface	Open API for software integration, including VAPIX [®] and AXIS Camera Application Platform; specifications at axis.com AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF [®] Profile G, ONVIF [®] Profile S, and ONVIF [®] Profile T, specification at onvif.org Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems, peer to peer or integrated with SIP/PBX.	
Analytics	Included AXIS Video Motion Detection, tampering alarm Supported AXIS Fence Guard, AXIS Motion Guard, AXIS Loitering Guard Support for AXIS Camera Application Platform enabling installation of third-party applications, see axis.com/acap	
Event triggers	Analytics, Edge storage events, Virtual inputs through API	
General		
Casing	IP66- and NEMA 4X-rated, IK08 impact-resistant casing Encapsulated electronics and captive screws (Torx 10) Color: white NCS S 1002-B For repainting instructions and impact on warranty, contact your Axis partner	
Sustainability	PVC free	
Memory	512 MB RAM, 512 MB Flash	
Power	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 3 Typical: 3.7 W, Max.: 7 W	
Connectors	RJ45 10BASE-T/100BASE-TX PoE Audio and I/O connectivity via the optional AXIS T61 Audio and I/O Interfaces with portcast technology	
IR illumination	Power-efficient, long-life 850 nm IR LED. Range of reach 20 m (65 ft) or more depending on the scene	
Storage	Support for microSD/microSDHC/microSDXC card and encryption Recording to network-attached storage (NAS) For SD card and NAS recommendations see axis.com	
Operating conditions	-30 °C to 50 °C (-22 °F to 122 °F) Start-up temperature: -20 °C to 50 °C (-4 °F to 122 °F) Humidity 10–100% RH (condensing)	
Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)	
Approvals	EMC EN 55024, EN 55032 Class A, EN 55035, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, KC KN32 Class A, KC KN35, RCM AS/NZS CISPR 32 Class A, ICES-3(A)/NMB-3(A), VCCI Class A Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-78, IEC 60068-2-14, IEC 60068-2-6, IEC 60068-2-27 IEC/EN 62262 IK08, IEC/EN 60529 IP66, NEMA 250 Type 4X Safety IEC/EN/UL 60950-22, IEC/EN/UL 62368-1, IEC/EN 62471, IS 13252 Network NIST SP500-267, IPv6 USGv6	
Dimensions	Height: 94 mm (3.7 in) ø 101 mm (4.0 in)	
Weight	390 g (0.85 lb)	
Included accessories	Installation Guide, Windows decoder 1-user license, Torx [®] L-key, Connector guard, Cable gasket	
Optional accessories	AXIS T94B02D Pendant kit, AXIS T94B01P Conduit Back Box, AXIS T94B02M J-Box/Gang Box Plate, AXIS TM3807 Black Casing, Axis Mounts, AXIS Surveillance microSDXC [™] Card, AXIS Weathershield Kit C, AXIS T61 Audio and I/O Interface Series For more accessories, see axis.com	
Video management software	AXIS Companion, AXIS Camera Station, Video management software from Axis' Application Development Partners available on axis.com/vms	
Languages	English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese	
Warranty	5-year warranty, see axis.com/warranty	

a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (www.openssl.org), and cryptographic software written by Eric Young (ey@cryptsoft.com).

Environmental responsibility:

